



CPCOMMUNICATIONS
NY • FL • CA

FOSTEX 6301B SPECIFICATIONS

Fostex



SPEAKER (Internal)

Type 10cm Full Range Single Cone
Impedance 4 Ω
Efficiency 84 dB/W (1m)

AMPLIFIER

Normal Input Level -10dBV
Output more than 10Wrms (8 Ω load)
Frequency Response 20 ~ 50 kHz +0dB-3dB
Distortion 0.05 % or less (at 1W output)
Residual Noise -70dBV (0.3mV)
Input Sensitivity Unbalanced type: -6dBV (0.5Vrms)
Balanced type: +4dBm (1.2Vrms)
Input Impedance Unbalanced type: Higher than 20k Ω
Balanced type: Higher than 10k Ω

GENERAL

Dimensions 120 (W) \times 188 (H) \times 118 (D) mm
Weight 3.0 kg
Power supply
JAPAN 100 VAC, 50/60 Hz
USA/CND 120 VAC, 60 Hz
EUR/UK 230 VAC, 50/60 Hz
Power consumption 33 W

phone 914-379-1700
toll free 800-762-4254
fax 914-423-6689

NY

407-843-4225
800-373-6827
407-843-4921

FL

818-954-9970
800-385-3331
818-954-9969

CA